

FULGOR

MILANO

600 Series PRO 30" Self Cleaning Double Wall Oven

F6PDP30S1



Series

600 PROFESSIONAL

Type

PYRO

Size

30"x30"

Colour

SS

Stainless Steel Aesthetics

Embossed window profile with bended edges

Oven Type

Multifunction 2 Fans (True Euro Convection)

Temperature Regulation

Electronic

Functions

Pyrolytic Self-Clean with automatic door latch



Upper/Lower

True European Convection Bake (Multi level)



Upper/Lower

Convection Broil



Upper/Lower

Convection Roast



Upper/Lower

Pizza (Lower Convection)



Upper/Lower

Bake



Upper/Lower

Broil



Upper/Lower

Dehydrate



Upper/Lower

Thaw (Defrost)



Upper/Lower

Proof (Warm)



Upper/Lower

Keep warm (Warm Plus)



Upper/Lower

Oven Lights



Upper/Lower

Fast Preheat



Upper/Lower

Control Panel

Control type

HAWK3TC - Electronic

Clock/Timer Display

White LED

Temperature Display

White LED

Function Display

White LED

Commands

2 Knobs / 6 Touch Keys

FULGOR

MILANO

Language	English
Special Features	
Preset/Last used temperature memory	•
Preheat bar (25%, 50%, 75%, 100%)	•
Automatic Fast Preheat	•
Child Door Lock	•
Commands Lock	•
Sabbath mode	•
12/24 hour clock format	•
°C/°F	•
Oven Door(s)	
Oven Glass Window	Large See Through Glass
Door Cooling System	4 Pane Heat Resistant Glass
Door Hinges	Heavy Duty Steady Tilt
Handle Style	Stainless Steel Tube d25mm, Plastic terminals
Oven Cavity	
Gross Capacity (cuft)	4.4
Usable Capacity (cuft)	4.1
Cavity Enamel Colour	Black
Rack Positions	6
Oven Lights	3x20W Halogen
Broil Upper Heating Element	3500 W (240V)
Upper Auxiliary Element Wattage	1032W (240V)
Concealed Bake Lower Heating Element	3000 W (240V)
Convection Element Wattage	2x1300 W (240V)
Oven Accessories	
Chromed racks	2 per cavity
Enameled Grill set (basin + anti splash)	1 per cavity
Telescopic chromed rack	1 per cavity
Meat probe	Upper Oven Only
Dimensions	
Overall dim - width	29 11/16" (754mm)
Overall dim - height	51" (1295mm)
Overall dim - depth	24" (610mm)
Cutout - width	28 7/16" (722mm)
Cutout - height (min)	50" (1270mm)
Cutout - depth (min)	23 1/4" (590mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 240V, 60Hz	7.68kW - 33.8A
KW/Amps rating at 208V, 60Hz	6.48kW - 32.4A
Cable + Conduit	•
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR